

Prepared by Richard C. Calderwood, Reg. No. 35,468

UNITED STATES PATENT APPLICATION

Title:

**FRONT END TRAIL ADJUSTMENT FOR MOTORCYCLE**

Inventors:

Michael Czysz

“Express mail” label no. EU580770321US

# FRONT END TRAIL ADJUSTMENT FOR MOTORCYCLE

## Background of the Invention

### Technical Field of the Invention

This invention relates generally to front end suspension components for two-wheeled vehicles, and more specifically to a trail adjustment mechanism such as for a motorcycle.

### Background Art

Trail is the distance, on the ground, from a point projected through the front axle on a line parallel with the steering axis, to a point directly below the front axle, or in other words, to the center of the contact patch. Trail directly impacts the steering stability of the motorcycle and its “return-to-center” force. Trail is affected by rake, which is the angle between vertical and the steering axis; steeper rake reduces trail. Trail is also affected by longitudinal fork offset, or the distance which the fork tubes are set in front of the steering tube; more offset increases trail. Trail is also affected by axle offset; if the axle is coupled to the forks in front of their center, it increases trail.

The rider may wish to increase or decrease trail to, for example, change the steering feel or feedback, to improve steering quickness, or to eliminate a high-speed wobble, or to reduce a front end “push”. Often, riders will talk as though they are fixing these things by adjusting the ride height, which is generally discussed in terms of how far the forks extend up through the top triple clamp. However, decreasing front ride height by raising the forks farther through the triple clamps in reality steepens the rake, which, in turn, decreases trail. It is ultimately the change in trail which causes the effects which the rider attributes to his ride height adjustment.

Although adjusting trail can have very beneficial results, the other changes which go along with it in a conventional motorcycle may often – or even usually – outweigh or significantly counteract the benefits of the trail adjustment. For example, lowering ride height obviously puts the frame, engine cases, fairings, and other parts into closer proximity to the racetrack, often to an extent that cornering ability is actually reduced because hard parts of the motorcycle ground out on curbing or even the asphalt itself.

1           What is needed, then, is a mechanism which facilitates trail adjustments without  
2           adversely affecting other geometry characteristics of the motorcycle such as ride height and rake  
3           angle.

#### 4                                   **Brief Description of the Drawings**

5           The invention will be understood more fully from the detailed description given below  
6           and from the accompanying drawings of embodiments of the invention which, however, should  
7           not be taken to limit the invention to the specific embodiments described, but are for explanation  
8           and understanding only.

9           FIG. 1 shows one embodiment of a motorcycle front end equipped with the trail  
10          adjustment mechanism of the present invention.

11          FIGS. 2-4 show the trail adjustment mechanism with three different trail adjustment  
12          blocks installed, to achieve three different amounts of trail.

13          FIG. 5 shows further details of the trail adjustment system.

14          FIGS. 6-7 show rear views of the brake caliper mounting system of the present invention,  
15          with the caliper aligned normally in FIG. 6 and swung out in FIG. 7 such as for clearance in  
16          unmounting a wheel assembly.

17          FIG. 8 shows one embodiment of a caliper mount such as may be used with the front end  
18          in conjunction with the trail adjustment system.

19          FIG. 9 shows a motorcycle equipped with the trail adjustment mechanism in its front end.

#### 20                                   **Detailed Description**

21          FIG. 1 illustrates a motorcycle front end 10 including a pair of telescopic forks 12  
22          rotatably coupled to a frame steering tube 14 by an upper triple clamp 16 and a lower triple  
23          clamp 18. The forks include trail adjustment blocks 20 which secure the front axle 22 to the forks  
24          at a predetermined offset with respect to the axis of the steering tube, which in turn dictates a  
25          predetermined amount of trail. A wheel 24 and tire 26 are coupled to the front axle.

26          FIGS. 2-4 illustrate the front end with three different trail blocks installed, producing  
27          three different amounts of trail. In FIG. 2, the fork 12 is equipped with a first trail adjustment  
28          block 20A which provides a first amount of trail. For the sake of convenience, the trail is  
29          represented simplistically as the distance from the axial center of the front axle to the back of the

1 trail adjustment block, rather than as a distance on the ground, but the reader will readily  
2 appreciate that the two are interrelated. In the instance of FIG. 2, the trail block offset is 1.37  
3 inches, corresponding to 3.5 inches of trail. The brake caliper 28 is mounted to the fork with a set  
4 of first caliper mounts 30A, which are sized to provide a particular distance from the center of  
5 the front axle to the brake pads (not shown). In FIG. 3, the fork 12 is equipped with a second trail  
6 adjustment block 20B with a trail block offset of 1.58 inches, corresponding to 3.75 inches of  
7 trail. The brake caliper 28 is mounted with a set of second caliper mounts 30B which are sized to  
8 provide the same distance from the center of the front axle, which has been moved forward  
9 relative to its position in FIG. 2, to the brake pads, so the brake pads maintain the same relative  
10 position with respect to the brake rotors (not shown, but which will have moved forward along  
11 with the front axle). In FIG. 4, the fork 12 is equipped with a third trail adjustment block 20C  
12 with a trail block offset of 1.83 inches, corresponding to 4.0 inches of trail, and the brake caliper  
13 is mounted with a set of third caliper mounts 20C to keep the same distance from the axle to the  
14 brake pads.

15 It should again be noted that, in one embodiment, the trail adjustment blocks and their  
16 mating surface of the fork lower are configured such that the front axle is moved, by the various  
17 trail adjustment blocks, in a direction parallel to the ground, such that the front ride height is not  
18 changed by swapping out the different trail adjustment blocks. In one embodiment, this is  
19 accomplished by providing the trail adjustment block with a top surface and a bottom surface  
20 which are parallel, and by positioning the front axle hole at various positions, for the various trail  
21 adjustment blocks, which are a same distance from the bottom surface, for example. In other  
22 embodiments, other geometries may accomplish the same result.

23 The trail adjustment block may be tightened onto the axle, and the fork lower may be  
24 tightened onto the trail adjustment block, by one or more pinch bolts (not shown) which may  
25 advantageously be inserted upward through the bottom end of the fork lower through coaxial  
26 holes (not shown) through the portion of the fork lower which is below the trail adjustment  
27 block, the portion of the trail adjustment block which is below the pinch split, the portion of the  
28 trail adjustment block which is above the pinch split, and the portion of the fork lower which is  
29 above the trail adjustment block. In this instance, only the topmost or two topmost of these need  
30 to be threaded.

1 In one embodiment, the brake caliper is mounted not only “radially”, but also with its  
2 radius parallel to the plane in which the various trail adjustment blocks move the front axle, to  
3 maintain a constant positioning of the brake pads and the brake rotor across the various trail  
4 settings. In one embodiment, the radius of the brake caliper mount is parallel to the ground.

5 FIG. 5 illustrates further details of the trail adjustment block 30 and the lower end of the  
6 fork 12, specifically illustrating one mechanism by which axial alignment can be achieved. The  
7 fork is illustrated in a truncated fashion, for simplicity. The trail adjustment block includes a top  
8 surface 40 and a parallel bottom surface (not visible) which, respectively, mate with a top surface  
9 (not visible) and a parallel bottom surface 42 of the fork. The back surface 44 of the trail  
10 adjustment block mates with a back surface 46 of the fork lower. These matings provide  
11 up-and-down and forward-backward alignment of the trail adjustment block with respect to the  
12 fork lower. In one embodiment, in order to provide positive and consistent lateral alignment  
13 (with respect to the front axle, not shown, but centered in the axle mounting hole 48), the upper  
14 and lower surfaces of the trail adjustment block are adapted with parallel grooves 50 which mate  
15 with corresponding parallel ridges 52 on the lower and upper surfaces of the fork. Other  
16 embodiments are certainly viable, such as swapping the grooves and the ridges, or one of each,  
17 or by using mounting pins and holes, or simply by using the corresponding pinch bolt holes 54,  
18 56 and the pinch bolt (not shown).

19 FIGS. 6 and 7 illustrate yet another advantageous feature of this front end. The brake  
20 caliper 28 is mounted to the fork 12 by a pair of caliper mounts 30 which can pivot with respect  
21 to the fork. Nuts 60 fasten the brake caliper onto the caliper mounts. In FIG. 6, the brake caliper  
22 is shown in a “straight back” configuration, such as it would be when the wheel and brake rotor  
23 are in place and the brake caliper is engaged with the rotor. In FIG. 7, the brake caliper is shown  
24 in a “swung out” configuration, which enables removal of the wheel/tire assembly (not shown),  
25 which will typically be wider than the distance between the left and right (not shown) brake  
26 calipers. To install the wheel/tire/rotor assembly, the calipers are swung outward, the wheel/tire  
27 assembly is inserted from the front of the motorcycle (in a direction coming out of the page in  
28 FIGS. 6 and 7) until the tire and/or wheel have cleared the rearward edge of the calipers but the  
29 rotors have not yet reached the calipers, the calipers are swung back straight, and the  
30 wheel/tire/rotor assembly is inserted the rest of the way into position, with the rotors correctly



1 entering the calipers between the pads, until the trail adjustment blocks encounter the back of  
2 their mating surface on the fork lowers. Then the pinch bolts can be inserted and tightened, and  
3 the assembly is complete.

4 FIG. 8 illustrates one exemplary embodiment of a caliper mount 30. The caliper mount  
5 includes a first cylindrical post 70 which mates with a corresponding hole in the fork (not shown)  
6 up flush with the face 72, and a second cylindrical post 74 which mates with a corresponding  
7 hole in the brake caliper (not shown) up flush with the face 76. In one embodiment, the two posts  
8 are at right angles to each other. In one embodiment, the brake caliper includes two parallel holes  
9 for accepting the posts 74 of two caliper mounts, and the fork lower includes two coaxial holes  
10 for accepting the posts 70 of the two caliper mounts, to facilitate pivoting of the brake caliper  
11 about the common axis of the posts 70 of the two caliper mounts. The post 74 may be adapted  
12 with threads or other suitable mechanism for retaining the caliper mount in engagement with the  
13 brake caliper, such as with the nut (not shown) mentioned above. The distance from the axis of  
14 the first post 70 to the flush mounting surface 76 of the second post dictates the trail adjustment  
15 provided by the caliper mount. In the example shown, the distance is 1.26 inches. When a  
16 "longer trail" adjustment block is used, such as when swapping from FIG. 2 to FIG. 4, a  
17 correspondingly shorter caliper mount will be used, to maintain correct alignment of the pads  
18 and rotor.

19 The skilled reader will readily appreciate that the various components of the caliper  
20 mount are not necessarily shown to any particular scale, and that they may be resized and  
21 adapted according to the needs of the application at hand. For example, the two posts need not  
22 necessarily be of the same diameter, or the post 70 could be made longer than shown, and so  
23 forth.

24 FIG. 9 illustrates one embodiment of a motorcycle 100 equipped with a front end 10  
25 having forks 12 equipped with the trail adjustment mechanism of the present invention, including  
26 the fork trail adjustment block 20.

## 27 Conclusion

28 While the invention has been described with reference to its use in a motorcycle, the  
29 invention is not limited to motorcycles, but can be used in bicycles, automobiles, and other  
30 vehicles. And while the invention has been shown as using an "upside-down" fork, it may

1 alternatively be used with a “right-side-up” fork. Some components have been illustrated as  
2 being of monolithic construction, while other components have been illustrated as being separate  
3 components coupled together. The skilled reader will readily appreciate that the designer may  
4 elect, within the scope of this invention, to split some components into separate sub-components,  
5 or to combine various components into a monolithic whole. The skilled reader will further  
6 appreciate that the invention may be practiced in a “single-sided” front end, such as that found  
7 on some bicycles which have only a single fork. The term “triple clamp” should not necessarily  
8 be interpreted to mean that two forks are required with the steering tube. The presence of one or  
9 more suspension components coaxial with the steering axis does not necessarily prohibit the  
10 additional presence of one or more suspension components elsewhere, such as within the forks.

11 The fork and the trail adjustment block have been illustrated in a configuration in which  
12 the trail adjustment block slips into the front of the fork. In other embodiments, a different  
13 mating system could be employed. For example, instead of a void or indentation formed into the  
14 front of the fork, the fork could have a hole extending laterally through it, or, in other words,  
15 there could be fork material in front of the void, and the trail adjustment block would be inserted  
16 laterally rather than longitudinally.

17 When one component is said to be “adjacent” another component, it should not be  
18 interpreted to mean that there is absolutely nothing between the two components, only that they  
19 are in the order indicated. The various features illustrated in the figures may be combined in  
20 many ways, and should not be interpreted as though limited to the specific embodiments in  
21 which they were explained and shown. Those skilled in the art having the benefit of this  
22 disclosure will appreciate that many other variations from the foregoing description and  
23 drawings may be made within the scope of the present invention. Indeed, the invention is not  
24 limited to the details described above. Rather, it is the following claims including any  
25 amendments thereto that define the scope of the invention.